


Specifications

MODELS	DPL™-25S		DPL™-30S		DPL™-35S	
MEASUREMENTS	US	Metric	US	Metric	US	Metric
Working height*	31 ft 4 in	9.70 m	36 ft	11.14 m	40 ft 9 in	12.59 m
Platform height	25 ft 4 in	7.70 m	30 ft	9.14 m	34 ft 9 in	10.59 m
Height - stowed	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
Length - stowed	6 ft 9.75 in	2.08 m	6 ft 9.75 in	2.08 m	6 ft 9.75 in	2.08 m
Width	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m



PRODUCTIVITY							
Lift capacity:	ANSI (Domestic)	750 lbs	340 kg	750 lbs	340 kg	600 lbs	272 kg
	CE (European)	750 lbs	340 kg	750 lbs	340 kg	600 lbs	272 kg
	CSA (Canadian)	600 lbs	272 kg	600 lbs	272 kg	500 lbs	227 kg

ANSI							
Outrigger footprint:							
A length	6 ft 10 in	2.08 m	7 ft 2.25 in	2.19 m	7 ft 2.25 in	2.19 m	
B width	4 ft 8.5 in	1.44 m	5 ft 8.75 in	1.75 m	5 ft 8.75 in	1.75 m	
C corner access	1 ft 5 in	.43 m	2 ft	.61 m	2 ft	.61 m	
D wall access front	7 in	.18 m	9 in	.23 m	9 in	.23 m	
E wall access side	1 ft 4 in	.41 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m	

CSA							
Outrigger footprint:							
A length	7 ft 5 in	2.26 m	7 ft 9 in	2.36 m	7 ft 9 in	2.36 m	
B width	6 ft 4.25 in	1.94 m	7 ft 2 in	2.18 m	7 ft 2 in	2.18 m	
C corner access	2 ft 5 in	.74 m	2 ft 10 in	.86 m	2 ft 10 in	.86 m	
D wall access front	11 in	.28 m	1 ft 1 in	.33 m	1 ft 1 in	.33 m	
E wall access side	2 ft 3 in	.69 m	2 ft 7 in	.79 m	2 ft 7 in	.79 m	

CE							
Outrigger footprint:							
A length	6 ft 10 in	2.08 m	7 ft 2.25 in	2.19 m	7 ft 2.25 in	2.19 m	
B width	4 ft 8.5 in	1.44 m	5 ft 8.75 in	1.75 m	5 ft 8.75 in	1.75 m	
C corner access	1 ft 5 in	.43 m	2 ft	.61 m	2 ft	.61 m	
D wall access front	7 in	.18 m	9 in	.23 m	9 in	.23 m	
E wall access side	1 ft 4 in	.41 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m	

Platform length	6 ft	1.83 m	6 ft	1.83 m	6 ft	1.83 m
Platform width	2 ft 3.5 in	.70 m	2 ft 3.5 in	.70 m	2 ft 3.5 in	.70 m

POWER	
Power source: AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12 V

WEIGHT**						
AC	1,375 lbs	624 kg	1,475 lbs	669 kg	1,575 lbs	714 kg
DC	1,450 lbs	658 kg	1,550 lbs	703 kg	1,650 lbs	748 kg

STANDARDS COMPLIANCE ANSI A92.3, CSA B354.1, CE Compliance, AS 1418.10, PB-10-611-03

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Weight will vary depending on options and/or country standards

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM

- 6 ft x 2 x 3.5 in (1.83 m x .70 m)

POWER OPTIONS

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 12V / 190 amp battery

STANDARD FEATURES

MEASUREMENTS

DPL™-25S

- 31 ft 4 in (9.70 m) working height
- 25 ft 4 in (7.70 m) platform height
- 2 ft 7.5 in (.80 m) base width
- 600-750 lb (272-340 kg) lift capacity

DPL™-30S

- 36 ft (11.14 m) working height
- 30 ft (9.14 m) platform height
- 2 ft 7.5 in (.80 m) base width
- 600-750 lb (272-340 kg) lift capacity

DPL™-35S

- 40 ft 9 in (12.59 m) working height
- 34 ft 9 in (10.59 m) platform height
- 2 ft 7.5 in (.80 m) base width
- 500-600 lb (227-272 kg) lift capacity

PRODUCTIVITY

- Large platform with room for 1-2 workers
- Auxiliary platform lowering
- Most rigid mast in the industry
- Durable base system
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt lower receptacle
- Patented outrigger interlock system
- Outrigger storage sockets
- Swivel-lock caster
- Tie down attachment points
- Rear access forklift pocket
- Angled entry ladder
- LED lights confirm proper set-up of outriggers
- Winch attachment points
- Locking key switch

POWER

- DC models include a 15 amp charging system with 110V / 50-60 Hz or 220V / 50-60 Hz input voltage



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Operational working light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

POWER

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 12V 190 Amp battery

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730

Telephone **(425) 881-1800**
Toll Free in USA/Canada **800-536-1800**
Fax (425) 883-3475

Genie Europe

The Maltings
Wharf Road
Grantham NG31 6BH
U.K.

Telephone **+44 (0)1476 584333**
Fax +44 (0)1476 584334

Email: infoeurope@genieind.com

Distributed By:

For further information, please contact your local distributor or the Genie Industries sales office listed. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. Genie makes no other warranty, expressed or implied. Products and services listed may be trademarks, service marks or trade-names of TEREX Corporation and/or its subsidiaries in the USA and other countries and all rights are reserved. Copyright © 2006 Genie Industries, Inc. "Genie" is a Registered Trademark of Genie Industries, Inc. in the USA and many other countries. Genie is a TEREX Company.